

Go in TiDB

申砾@PingCAP





Agenda


- About Me
- What is TiDB
- TiDB Architecture
- SQL Layer Internal
- Golang in TiDB
- Next Step of TiDB

About Me

- Shen Li (申砾)
- Tech Lead of TiDB, VP of Engineering
- Netease / 360 / PingCAP
- Infrastructure software engineer


What is TiDB

A **Distributed, Consistent, Scalable, SQL** Database that supports the best features of both traditional RDBMS and NoSQL.




GopherChina 2017

Architecture - the Whole Picture



Architecture - SQL Layer



Example - SQL


Schema:

CREATE TABLE t (c1 INT, c2 VARCHAR(32), INDEX idx1 (c1));


Query:

SELECT COUNT(c1) FROM t WHERE c1 > 10 AND c2 = "gopherchina";


Example - Logical Plan



Example - Physical Plan




Example - Distributed Physical Plan



Challenges in Building a Distributed Database

- A very complex distributed system
- A lot of RPC work
- High performance
- Tons of data
- Huge amount of OLTP queries
- Very complex OLAP queries



Why Go?

- Productivity
- Concurrency
- Great for network programming
- GC
- Standard libraries && Tools
- Good performance
- Quick improvement

Go in TiDB


More than 100k lines of Go code and 94 contributors.

Language	files	blank	comment	code
Go yacc YAML make Bourne Shell	457 1 3 1 4	13924 363 4 33 12	14782 227 0 2	112255 6021 191 102 53
SUM:	466	14336	15016	118622


Goroutine

- Starting a goroutine is easy and cheap.
- Goroutines come with built-in primitives to communicate safely between themselves (channels).
- Very easy to write concurrent programs.
- Make full use of multi-core processors.

Parallel Data Scan Operator



Parallel HashJoin Operator



Goroutine Leak

- Write to a chan with no reader.
- Read from a chan with no writer.
- How to resolve?
 - Block profile
 - Timeout
 - Context

Goroutine Leak Test

A useful tool from net/http

github.com/pingcap/tidb/util/testleak

```
Usage:
func (s testMiscSuite) TestRunWithRetry(c *C) {
  defer testleak.AfterTest(c)()
    ......
}
```

Memory && GC

Query may touch a huge number of data.

So we should take care of the memory.

- Degrade the performance of SQL.
- OOM sucks!

Reduce the Number of Allocation

Get enough memory in one allocation operation

```
a := []int{1, 2, 3, 4, 5}
b := []int{}
// a much better way:
// b := make([]int, 0, len(a))
for _, i := range a {
    b = append(b, i)
}
```

Reuse Object

- Introduce a cache in goyacc
- Share a stack for all queries in one session

Before:

insert test data finished ... elapse: 34.563343s tps:28932.386438

After:

insert test data finished ... elapse: 28.859153s tps:34651.051825

sync.Pool

- Thread safe
- Reuse objects to relieve pressure on the GC.
- Case study: bytes pool

Test on a query reads 1 million rows

```
Before After
# runtime.MemStats # runtime.MemStats
# Alloc = 1985803616 # Alloc = 1303384504
# TotalAlloc = 4365147096 # TotalAlloc = 1676585832
```

gogo/protobuf

- Fast marshalling and unmarshalling
- Fields without pointers cause less time in the garbage collector.
- Used by etcd/docker/k8s/tidb
- Benchmark

Monitor the Memory Usage

- Monitor the memory usage of the server is easy
 - runtime.MemProfile()
- Monitor the memory usage of a session is hard
 - Account for large memory allocation
 - Account for memory consuming operators

New in Go1.8

- Better GC
 - Pauses 50µs
- sort.Slice

```
Benchmark100Slice-4
                                  2000000
                                                         630 ns/op
Benchmark100Sort-4
                                   300000
                                                        4784 ns/op
Benchmark1000Slice-4
                                                        3988 ns/op
                                   300000
Benchmark1000Sort-4
                                                      108745 ns/op
                                    10000
Benchmark10000Slice-4
                                                     1228942 ns/op
                                     1000
Benchmark10000Sort-4
                                                     1440223 ns/op
                                     1000
Benchmark100000Slice-4
                                                    14483929 ns/op
                                      100
Benchmark100000Sort-4
                                      100
                                                    17661242 ns/op
```

Next Step of TiDB

- Switch to gRPC
- Document support
- Statistic && CBO (Cost-based Optimizer)
- Better optimizer
- Faster and more general execution engine
- TiDB + Spark = TiSpark

Thanks!

We are hiring! shenli@pingcap.com

May all the data find their own place,
May all the SQL queries speed up!
Come, and join us,
To make the best NewSQL database!



